Blackbird Micro Half Sph…

1 variant

Blackbird Micro Half Sphere Facade is a professional LED outdoor luminaire from VIZULO for facade and entrance lighting.

TECHNICAL DATA

ELECTRONICS	
Primary voltage	198 - 264 V
Frequency	50 - 60 Hz
Power range	5 - 8 W
Surge protection	4 / 6 / 10 kV
LIGHTING TECHNOLOGY	
Colour temperature	2'700 K, 3'000 K, 4'000 K
Special colour temperatures	1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)
Colour rendering	>80 / >90
Maximum colour deviation	MacAdam 5
Lifetime	Up to 100'000 h (L90B10) at Ta = 25 °C
Dimmability	DALI / Not dimmable
DIMENSIONS & MATERIAL	
Housing colours	Silver RAL9006, Asphalt DB703, Black RAL9005, RAL7035, further RAL colours on request
Luminaire body	die-cast aluminium
FURTHER DATA	
Operating temperature	-40 to +50 °C
Warranty	5-10 years
Corrosion protection	Up to C5
Mounting	On the wall

Qualitätsmitglied des Fachverbandes der Beleuchtungsindustrie

VARIANTS

65.09423.H17969 Blackbird Micro Half Sphere Facade

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.

Qualitätsmitglied des Fachverbandes der Beleuchtungsindustrie