

Blackbird Micro Outdoor ...

1 variant



Blackbird Micro Outdoor Ceiling is a professional LED outdoor luminaire from VIZULO for canopies, passages and outdoor areas of buildings.

TECHNICAL DATA

ELECTRONICS

Primary voltage	198 - 264 V
Frequency	50 - 60 Hz
Power range	5 - 12 W
Surge protection	4 / 6 / 10 kV

LIGHTING TECHNOLOGY

Colour temperature	2'700 K, 3'000 K, 4'000 K
Special colour temperatures	1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)
Colour rendering	>70 / >80 / >90
Maximum colour deviation	MacAdam 5
Lifetime	Up to 100'000 h (L90B10) at Ta = 25 °C
Dimmability	DALI / Not dimmable

DIMENSIONS & MATERIAL

Housing colours	Silver RAL9006, Asphalt DB703, Black RAL9005, RAL7035, further RAL colours on request
Luminaire body	die-cast aluminium

FURTHER DATA

Operating temperature	-40 to +50 °C
Warranty	5-10 years
Corrosion protection	Up to C5
Mounting	On the ceiling

VARIANTS

65.09424.H17970 Blackbird Micro Outdoor Ceiling

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.