Blackbird Mini Hanging T...

1 variant

The original Blackbird quickly became a favourite - its clean lines and timeless design, unmistakable yet always fitting, make it the ideal choice for any architectural environment. With the Blackbird Mini we have gone one step further. In a meticulous process we removed everything superfluous and refined even the smallest details to the highest level. The boundaries between pole, bracket and luminaire blur until they form a single unit.The result?

TECHNICAL DATA

ELECTRONICS

Primary voltage	198 - 264 V
Frequency	50 - 60 Hz
Power range	5 - 30 W
Interfaces	NEMA-top / Zhaga-top
Surge protection	4 / 6 / 10 kV

LIGHTING TECHNOLOGY

Colour temperature	2'700 K, 3'000 K, 4'000 K
Special colour temperatures	1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)
Colour rendering (CRI)	>70 / >80 / >90
Maximum colour deviation	MacAdam 5
Lifetime	up to 100'000 h (L90B10) at Ta = 25 °C
Dimmability	DALI / 1-10 V / Midnight Dimming / Phase Dimming / Mains Dimming

DIMENSIONS & MATERIAL

Housing colours	Mica 3602 MF/MA, further RAL colours on request
Luminaire body	die-cast aluminium

FURTHER DATA

Operating temperature	-40 to +50 °C

Qualitätsmitglied des Fachverbandes der Beleuchtungsindustrie

Warranty	5-10 years
Corrosion protection	up to C5
Mounting	on wire Ø 5 - 12 mm, tool-free

VARIANTS

65.09430.H17976 Blackbird Mini Hanging Toolless

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.

Qualitätsmitglied des Fachverbandes der Beleuchtungsindustrie