

Blackbird Mini Spot Brac...

1 variant



The original Blackbird quickly became a favourite - its clean lines and timeless design, unmistakable yet always fitting, make it the ideal choice for any architectural environment. With the Blackbird Mini we have gone one step further. In a meticulous process we removed everything superfluous and refined even the smallest details to the highest level. The boundaries between pole, bracket and luminaire blur until they form a single unit. The result?

TECHNICAL DATA

ELECTRONICS

Primary voltage	198 - 264 V
Frequency	50 - 60 Hz
Power range	5 - 30 W
Interfaces	external Zhaga-top and -bottom
Surge protection	4 / 6 / 10 kV

LIGHTING TECHNOLOGY

Colour temperature	2'700 K, 3'000 K, 4'000 K
Special colour temperatures	1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)
Colour rendering (CRI)	>70 / >80 / >90
Maximum colour deviation	MacAdam 5
Lifetime	up to 100'000 h (L90B10) at Ta = 25 °C
Dimmability	DALI / 1-10 V / Midnight Dimming / Phase Dimming / Mains Dimming

DIMENSIONS & MATERIAL

Weight	up to 3.5 kg
Housing colours	Mica 3602 MF/MA, further RAL colours on request
Luminaire body	die-cast aluminium

FURTHER DATA

Protection rating	IP66
Impact resistance	IK10
Operating temperature	-40 to +40 up to 30 W; -40 to +50 up to 20 W °C
Warranty	5-10 years
Corrosion protection	up to C5
Mounting	on ø 60 / 76 mm pole

VARIANTS

65.09432.H17978 Blackbird Mini Spot Bracket Mount

DOCUMENTS

Herstellerlink

Datenblatt

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.