

Heron

1 variant



Three different length options, two mounting types, one mission - to avoid the difficult choice between style and function on your car parks, pedestrian paths and other areas. The shorter version is a beautiful decorative addition to any outdoor space, while the longer version provides ample light for any type of landscape. The minimalist design is built for longevity and offers a few customisation options: you can choose the bracket with or without flange. Combine the ground-mounted HERON with our surface-mounted ROBIN luminaires to create a tasteful Scandinavian theme.

TECHNICAL DATA

ELECTRONICS

Primary voltage 220 - 240 V

Frequency 50 - 60 Hz

Power range 4 - 26 W

Surge protection 1 / 2 / 4 / 10 kV

LIGHTING TECHNOLOGY

Colour temperature 2'700 K, 3'000 K, 4'000 K

Special colour temperatures 1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)

Colour rendering >80 / >90

Maximum colour deviation MacAdam 5

Luminous flux 440 - 3'920 lm

Luminaire efficacy 106 - 151 lm/W

Light distribution E22, E63, E93 and others, further optics on request

Lifetime 100'000 h (L98B10) at Ta = 25 °C

Dimmability DALI / midnight dimming / phase dimming / mains dimming

DIMENSIONS & MATERIAL

Weight up to 4.8 kg / up to 15 kg

Housing colours Silver RAL9006, Asphalt DB703, Black RAL9005, Galvanized, further RAL colours on request

Luminaire body	extruded aluminium / steel
-----------------------	----------------------------

FURTHER DATA

Protection rating	IP65
Impact resistance	IK08
Operating temperature	-40 to +40 °C
Warranty	5-10 years
Certificates	CE, UKCA, RoHS
Corrosion protection	Up to C5
Mounting	on flange

VARIANTS

65.09467.H18050 Heron

DOCUMENTS

Datenblatt

Herstellerlink

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.