

Robin

1 variant



Bring balance and consistency to your space with these surface-mounted architectural luminaires. We developed ROBIN as a complement to our best-selling HERON luminaires, to design the most modern minimalist outdoor areas: car parks, pedestrian walkways, even pitched roofs and façades. ROBIN shines brightly, both literally and metaphorically, and allows you to express Nordic values through its design.

TECHNICAL DATA

ELECTRONICS

Primary voltage	220 - 240 V
Frequency	50 - 60 Hz
Power range	8 - 26 W
Surge protection	4 / 6 / 10 kV

LIGHTING TECHNOLOGY

Colour temperature	2'700 K, 3'000 K, 4'000 K
Special colour temperatures	1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)
Colour rendering (CRI)	>80 / >90
Maximum colour deviation	MacAdam 5
Luminous flux	913 - 3'350 lm
Luminaire efficacy	106 - 135 lm/W
Lifetime	Up to 100'000 h (L95B10), Ta = 25 °C
Dimmability	DALI / midnight dimming / Not dimmable

DIMENSIONS & MATERIAL

Weight	up to 1.1 kg
Wind load area	0.014 m²
Housing colours	Black RAL9005, further RAL colours on request
Luminaire body	die-cast aluminium

FURTHER DATA

Protection rating	IP66
Impact resistance	IK10
Operating temperature	-40 to +40 °C
Warranty	5-10 years
Corrosion protection	Up to C5
Mounting	On the wall

VARIANTS

65.9493.H18103 Robin

DOCUMENTS

Datenblatt

Herstellerlink

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.