

Rook

1 variant



In terms of design, the ROOK is another team player for all your HERON arrangements, but it can also deliver the performance of a king on its own! This powerful, surface-mounted outdoor luminaire can work wonders for your outdoor areas. With the ROOK, you can make your car parks and walkways safer or emphasise the beauty of your buildings with a few well-placed façade luminaires. Combine the ROOK with our ground-mounted HERON luminaires and enjoy world-class architectural design without breaking your budget.

TECHNICAL DATA

ELECTRONICS

Primary voltage	220 - 240 V
Frequency	50 - 60 Hz
Power range	15 - 28 W
Surge protection	4 / 6 / 10 kV

LIGHTING TECHNOLOGY

Colour temperature	2'700 K, 3'000 K, 4'000 K
Special colour temperatures	1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)
Colour rendering (CRI)	>80 / >90
Maximum colour deviation	MacAdam 5
Luminous flux	1'845 - 3'890 lm
Luminaire efficacy	119 - 143 lm/W
Lifetime	Eco 100'000 h (L90B10) at Ta = 25 °C / Standard / High density 100'000 h (L98B10) at Ta = 25 °C
Dimmability	DALI / 1-10 V / midnight dimming / phase dimming / mains dimming

DIMENSIONS & MATERIAL

Weight	up to 3.3 kg
Wind load area	0.015 m²
Housing colours	Black RAL9005, further RAL colours on request

Luminaire body	die-cast aluminium
----------------	--------------------

FURTHER DATA

Protection rating	IP65
Impact resistance	IK08
Operating temperature	-40 to +40 °C
Warranty	5-10 years
Certificates	CE, UKCA, RoHS
Corrosion protection	Up to C5
Mounting	On the wall

VARIANTS

65.09494.H18104 Rook

DOCUMENTS

Datenblatt

Herstellerlink

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.