Stork Little Sister Smoot…

1 variant



Like all products in the Stork family, Stork Little Sister is an elegant powerhouse with a perfect balance of performance and design. Despite its compact size, it delivers impressive performance and ensures well-lit streets and areas, regardless of their size.

TECHNICAL DATA

ELECTRONICS

Primary voltage	198 - 264 V
Frequency	50 - 60 Hz
Power range	5 - 96 W
Interfaces	NEMA-top / Zhaga-top and -bottom
Surge protection	4 / 6 / 10 kV

LIGHTING TECHNOLOGY

Colour temperature	2'700 K, 3'000 K, 4'000 K
Special colour temperatures	1'800 K, 2'200 K, 3'500 K, 5'000 K, 5'700 K, 6'500 K (on request)
Colour rendering	>70 / >80 / >90
Maximum colour deviation	MacAdam 5
Luminous flux	476 - 14'990 lm
Luminaire efficacy	95 - 181 lm/W
Light distribution	BC6, LC6, LC7, L35, L90 among others, further optics on request
Lifetime	Eco 100'000 h (L90B10) at Ta = 25 °C / Standard / High density 100'000 h (L98B10) at Ta = 25 °C
Dimmability	DALI / 1-10 V / midnight dimming / phase dimming / mains dimming

DIMENSIONS & MATERIAL

Length	763 mm
Width	170 mm

Qualitätsmitglied des Fachverbandes der Beleuchtungsindustrie

Height	104 mm
Weight	up to 5.8 kg
Wind load area	0.06 m²
Pole brackets (spigot)	Ø 32 - 40 mm / 40 - 60 mm / 60 - 76 mm
Housing colours	Silver RAL9006, Asphalt DB703, Black RAL9005, RAL7035, further RAL colours on request
Luminaire body	die-cast aluminium

FURTHER DATA

Protection rating	IP66
Impact resistance	IK09
Operating temperature	-40 to +55 °C
Warranty	5-10 years
Certificates	CE, UKCA, RoHS
Corrosion protection	up to C5
Mounting	pole/bracket mounting, tool-free

VARIANTS

65.09505.H18126 Stork Little Sister Smooth Extended

DOCUMENTS

Datenblatt
Montageinstruction

The technical data is not exhaustive; if you have any questions, please feel free to contact us at any time.

Qualitätsmitglied des Fachverbandes der Beleuchtungsindustrie