

Planea Midi WL

1 variant



The Planea Midi WL is a wall luminaire for outdoor lighting with a flat housing in aluminium profile (400 x 200 x 80 mm) and a stainless steel wall bracket. With BLK4 LED modules, the family covers three power levels (15.3/20.3/28 W) and delivers 1'076-3'665 lm at 3'000 K, depending on module and current. Four light distributions, the light colours 2'200/2'700/3'000 K (optionally 1'800/4'000 K) and three standard housing colours make the luminaire configurable for direct wall mounting.

TECHNICAL DATA

ELECTRONICS

Power	15.3 W / 20.3 W / 28 W
Control gear	constant-current driver for LED modules

LIGHTING TECHNOLOGY

Luminaire type	Wall luminaire
Light source	LED module type BLK4-3/4/5/8C or S
Light colour	2'200 K / 2'700 K / 3'000 K, optional 1'800 K / 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Colour rendering	CRI > 80 at 2'700 K / 3'000 K / 4'000 K, CRI > 70 at 1'800 K / 2'200 K
Rated luminous flux	1'076 - 3'665 lm at 3'000 K (depending on LED module and current 250/350/500 mA)
Light distribution	linear wide-beam / asymmetric wide-beam / asymmetric deep-beam
Cover	PMMA lenses, clear or satin-finished; bottom cover in clear PMMA

FUNCTIONALITY

Dimmability	AstroDim, 1-10 V; optionally DALI, DC-capable, dimming circuit (StepDim)
Application area	Outdoor

DIMENSIONS

Length	400 mm
Width	200 mm
Height	80 mm

MATERIAL

Housing colour	DB 703 / DB 702S / DB 701, further colours on request
Housing material	aluminium profile, coated surfaces
Light emission material	PMMA lenses, clear or satin-finished, bottom cover clear PMMA
Luminaire body	aluminium

FURTHER DATA

Protection rating	housing IP65, LED module IP67
Protection class	I and II
Warranty	5 years
Certificates	CE, LED module and LED driver ENEC-certified
Mounting	Wall mounting with a stainless steel wall bracket, optionally a bracket for mounting on Planea Midi LS

VARIANTS

65.09686.H18539 Planea Midi WL