

Planea Maxi WL

1 variant



The Planea Maxi WL is a wall luminaire for outdoor lighting with a housing in aluminium profile (650 x 240 x 100 mm) and a stainless steel wall bracket. The family can be equipped with 2, 3 or 4 BLK2 LED modules and covers three power levels (19/36/49 W). When fully equipped (4 modules) it delivers 3'340-5'616 lm at 3'000 K, depending on module and current. Four light distributions, the light colours 2'200/2'700/3'000 K (optionally 1'800/4'000 K) and three standard housing colours make the luminaire configurable for direct wall mounting.

TECHNICAL DATA

ELECTRONICS

Power 19 W / 36 W / 49 W

Control gear constant-current driver for LED modules

LIGHTING TECHNOLOGY

Luminaire type Wall luminaire

Light source 2, 3 or 4x LED module type BLK2-3/4/5/8C or S

Light colour 2'200 K / 2'700 K / 3'000 K, optional 1'800 K / 4'000 K

Light colour adjustable No

Power adjustable Yes

Rated luminous flux 3'340 - 5'616 lm at 3'000 K (at 4x LED module, depending on module and current 350/500 mA)

Light distribution linear wide-beam / asymmetric wide-beam / asymmetric deep-beam

Cover PMMA lenses, clear or satin-finished; bottom cover in clear PMMA

FUNCTIONALITY

Dimmability AstroDim, 1-10 V; optionally DALI, DC-capable, dimming circuit (StepDim)

Application area Outdoor

DIMENSIONS

Length	650 mm
Width	240 mm
Height	100 mm

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
Housing material	aluminium profile, coated surfaces
Light emission material	PMMA lenses, clear or satin-finished, bottom cover clear PMMA
Luminaire body	aluminium

FURTHER DATA

Protection rating	housing IP65, LED module IP67
Protection class	I and II
Warranty	5 years
Certificates	CE, LED module and LED driver ENEC-certified
Mounting	Wall mounting with a stainless steel wall bracket

VARIANTS

65.09688.H18541 Planea Maxi WL