

Street Loop I LS

1 variant



The Street Loop I LS is a ring-shaped bracket luminaire for outdoor lighting with a luminaire head and bracket in aluminium (Ø 1'100 mm) on a hot-dip galvanised and coated steel system column. Instead of individual LED modules, a flexible all-round LED strip (Osram LINEARlight FLEX Protect) with a microprismatic PMMA cover is used, delivering a total of 5'499 lm at 68 W. The light colour 3'000 K (optionally 4'000 K) and three standard housing colours make the luminaire configurable for light point heights of approx. 4.50-5.90 m.

TECHNICAL DATA

ELECTRONICS

Power	68 W
Control gear	24 V constant-voltage driver OSRAM OT100 24 DIM P

LIGHTING TECHNOLOGY

Luminaire type	Bracket luminaire
Light source	flexible LED strip, Osram LINEARlight FLEX Protect
Light colour	3'000 K, optional 4'000 K
Light colour adjustable	No
Power adjustable	Yes (dimmable 1-10 V)
Rated luminous flux	5'499 lm
Light distribution	symmetric wide-beam
Cover	microprismatic cover in PMMA

FUNCTIONALITY

Dimmability	1-10V
Application area	Outdoor

DIMENSIONS

Diameter (ring)	1'100 mm
Light point height	approx. 4.50 - 5.90 m (with system column)

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
Housing material	luminaire head and bracket in aluminium, coated surfaces
Light emission material	microprismatic cover in PMMA
Luminaire body	aluminium; system column in steel, hot-dip galvanised and coated

FURTHER DATA

Protection rating	housing IP65, LED module IP67
Protection class	I
Warranty	5 years
Certificates	CE, LED strip and LED power supply ENEC-certified
Mounting	Post-top mounting on a system column with ground section or flange plate

VARIANTS

65.09693.H18546 65.09693.H18546