

Planus I Midi ML

1 variant



The Planus I Midi ML is a column and wall luminaire for outdoor lighting with a housing in aluminium, optionally also in burnished bronze. It is equipped with 2x BLK4 LED module, covers a power of 39-55 W and delivers 3'854-6'218 lm depending on module. Four light distributions, the light colour 3'000 K (optionally 4'000 K) and three standard housing colours make the luminaire configurable for a fixed light point height of 6.00 m.

TECHNICAL DATA

ELECTRONICS

Power 39 - 55 W

Control gear OSRAM OT100 2DIM

LIGHTING TECHNOLOGY

Luminaire type Column and wall luminaire

Light source 2x LED module type BLK4-3/5/7/8C or S

Light colour 3'000 K, optional 4'000 K

Light colour adjustable No

Power adjustable Yes

Rated luminous flux 3'854 - 6'218 lm (depending on LED module)

Light distribution linear wide-beam / asymmetric wide-beam / asymmetric deep-beam

Cover PMMA lenses, clear or satin-finished

FUNCTIONALITY

Dimmability AstroDim, 1-10 V; optionally DALI, DC-capable, dimming circuit (StepDim)

Application area Outdoor

DIMENSIONS

Length (head) 164 mm

Height (head) 65 mm

Light point height	6.00 m
--------------------	--------

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), optionally burnished bronze, further colours on request
----------------	---

Housing material	aluminium or bronze, coated surfaces
------------------	--------------------------------------

Light emission material	PMMA lenses, clear or satin-finished
-------------------------	--------------------------------------

Luminaire body	aluminium
----------------	-----------

FURTHER DATA

Protection rating	housing IP44, LED module IP66
-------------------	-------------------------------

Protection class	I and II
------------------	----------

Warranty	5 years
----------	---------

Certificates	CE
--------------	----

Mounting	Post-top or wall mounting
----------	---------------------------

VARIANTS

65.09696.H18549	65.09696.H18549
-----------------	-----------------