

Freising ML

1 variant



The Freising ML is a classic lantern-style column and wall luminaire for outdoor lighting with a housing in stainless steel, optionally also in burnished bronze. The characteristic glass body with decorative rod and glass sphere is equipped with BLK4 LED modules and covers a power of 18.5-26 W. The light colours 2'700/3'000 K (optionally 1'800/2'200/4'000 K) and three standard housing colours make the luminaire configurable for a fixed light point height of 4.50 m.

TECHNICAL DATA

ELECTRONICS

Power	18.5 - 26 W
Control gear	OSRAM OT50 2DIM

LIGHTING TECHNOLOGY

Luminaire type	Column and wall luminaire (lantern)
Light source	LED module type BLK4-4/5/6/8S
Light colour	2'700 K / 3'000 K, optional 1'800 K / 2'200 K / 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Cover	PMMA lenses, satin-finished, optionally with a glare shield

FUNCTIONALITY

Dimmability	AstroDim, 1-10 V; optionally DALI, DC-capable, dimming circuit (StepDim)
Application area	Outdoor

DIMENSIONS

Width (head, square)	400 mm
Height (head)	660 mm
Light point height	4.50 m

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), optionally burnished bronze, further colours on request
Housing material	stainless steel or bronze, coated surfaces; optional trim ring in satin-finished PMMA
Light emission material	PMMA lenses satin-finished
Luminaire body	stainless steel

FURTHER DATA

Protection rating	housing IP54, LED module IP67
Protection class	I and II
Warranty	5 years
Certificates	CE, LED module and LED driver ENEC-certified
Mounting	Post-top or wall mounting

VARIANTS

65.09697.H18550 65.09697.H18550