

Grafiing I AL

1 variant



The Grafiing I AL is a bracket luminaire for outdoor lighting with a round, flat luminaire head in aluminium, optionally also in burnished bronze. The head is available with a decorative trim ring in satin-finished PMMA or, as required, without a ring. It is equipped with BLK4 LED modules, covers a power of 21-33 W and delivers 1'927-3'581 lm depending on module. The light colour 3'000 K (optionally 4'000 K) and three standard housing colours make the luminaire configurable for a fixed light point height of 5.00 m.

TECHNICAL DATA

ELECTRONICS

Power	21 - 33 W
Control gear	OSRAM OT50 2DIM

LIGHTING TECHNOLOGY

Luminaire type	Bracket luminaire
Light source	LED module type BLK4-3/4/5/8S
Light colour	3'000 K, optional 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	1'927 - 3'581 lm (depending on LED module)
Light distribution	linear wide-beam / asymmetric wide-beam / asymmetric deep-beam
Cover	PMMA lenses, satin-finished; optional decorative trim ring in PMMA, satin-finished

FUNCTIONALITY

Dimmability	AstroDim, 1-10 V; optionally DALI, DC-capable, dimming circuit (StepDim)
Application area	Outdoor

DIMENSIONS

Length (bracket, total)	868 mm
-------------------------	--------

Light point height	5.00 m
--------------------	--------

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), optionally burnished bronze, further colours on request
Housing material	aluminium or bronze, coated surfaces
Light emission material	PMMA lenses satin-finished, optional trim ring PMMA satin-finished
Luminaire body	aluminium

FURTHER DATA

Protection rating	housing IP54, LED module IP66
Protection class	I and II
Warranty	5 years
Certificates	CE, LED module and LED driver ENEC-certified
Mounting	Post-top mounting, wall mounting or suspension from a catenary

VARIANTS

65.09698.H18551 65.09698.H18551