

Grafiing II AL

1 variant



The Grafiing II AL is a generously sized design bracket and column luminaire with a round, flat luminaire head in burnished bronze, optionally also coated. Each luminaire head is equipped with 3x BLK3 LED module, covers a power of 42-59 W and delivers 4'335-6'993 lm depending on module. One to four luminaire heads can be combined on a wall or column. The light colour 3'000 K (optionally 4'000 K) and three standard housing colours make the luminaire configurable for a fixed light point height of 6.00 m.

TECHNICAL DATA

ELECTRONICS

Power per luminaire head	42 - 59 W
Control gear	OSRAM OT50/100 2DIM

LIGHTING TECHNOLOGY

Luminaire type	Bracket luminaire (wall or column mounting, 1 to 4 luminaire heads combinable)
Light source	3x LED module type BLK3-3/5/7/8S per luminaire head
Light colour	3'000 K, optional 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	4'335 - 6'993 lm (depending on LED module)
Light distribution	asymmetric wide-beam / asymmetric deep-beam
Cover	PMMA lenses, satin-finished; decorative trim ring in PMMA, satin-finished

FUNCTIONALITY

Dimmability	AstroDim, 1-10 V; optionally DALI, DC-capable, dimming circuit (StepDim)
Application area	Outdoor

DIMENSIONS

Length (bracket, total)	1'122 mm
-------------------------	----------

Light point height	6.00 m
--------------------	--------

MATERIAL

Housing colour	burnished bronze (standard); optionally coated in DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
----------------	--

Housing material	bronze, optionally coated surfaces
------------------	------------------------------------

Light emission material	PMMA lenses satin-finished, trim ring PMMA satin-finished
-------------------------	---

Luminaire body	bronze
----------------	--------

FURTHER DATA

Protection rating	housing IP65, LED module IP67
-------------------	-------------------------------

Protection class	I and II
------------------	----------

Warranty	5 years
----------	---------

Certificates	CE, LED module and LED driver ENEC-certified
--------------	--

Mounting	Post-top mounting, wall mounting or suspension from a catenary
----------	--

VARIANTS

65.09699.H18552	65.09699.H18552
-----------------	-----------------