

Tektus Midi

1 variant



The Tektus Midi is a classic bracket and column luminaire with a curved bronze arm, shade shell and luminaire glazing in clear PMMA. It is equipped with 1x BLK4 LED module, covers a power of 11.4-35.4 W and delivers up to 3'814 lm at 3'000 K. One to four luminaire heads can be combined on a column or wall. The light colours 2'200/2'700/3'000 K (optionally 1'800/4'000 K) and three standard housing colours make the luminaire configurable for a fixed light point height of 5.00 m.

TECHNICAL DATA

ELECTRONICS

Power	11.4 - 35.4 W
Control gear	LED DALI constant-current driver

LIGHTING TECHNOLOGY

Luminaire type	Bracket and column luminaire (1 to 4 luminaire heads combinable)
Light source	1x LED module type BLK4-3/4/8C or S
Light colour	2'200 K / 2'700 K / 3'000 K, optional 1'800 K / 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	up to 3'814 lm at 3'000 K (maximum value, depending on LED module)
Light distribution	linear wide-beam / asymmetric wide-beam / asymmetric deep-beam
Cover	PMMA lenses, clear or satin-finished; luminaire glazing in PMMA, clear

FUNCTIONALITY

Dimmability	AstroDim, DALI, DC-capable, dimming circuit (StepDim)
Application area	Outdoor

DIMENSIONS

Length (bracket, total)	1'010 mm
Light point height	5.00 m

MATERIAL

Housing colour	burnished bronze (standard); optionally coated in DB 703 / DB 702S / DB 701, further colours on request
Housing material	bronze, optionally coated surfaces
Light emission material	luminaire glazing clear PMMA, lenses PMMA clear or satin-finished
Luminaire body	bronze

FURTHER DATA

Protection rating	housing IP44, LED module IP66
Protection class	I and II
Warranty	5 years
Certificates	CE, LED module and LED driver ENEC-certified
Mounting	Post-top or wall mounting

VARIANTS

65.09700.H18553 65.09700.H18553