

Canna Q 200 LS

1 variant



The Q 200 LS is a square light bollard for outdoor lighting with a housing in hot-dip galvanised steel (200 x 200 mm) and luminaire glazing in clear PMMA. It combines a fixed LED module with an adjustable BLK2 LED module and covers a power of 11.4-35.4 W. The light colours 2'200/2'700/3'000 K (optionally 1'800/4'000 K) and three standard housing colours make the luminaire configurable; the datasheet quotes a light point height of 4.35 m as the reference height.

TECHNICAL DATA

ELECTRONICS

Power	11.4 - 35.4 W
Control gear	OSRAM OT40 4DIM

LIGHTING TECHNOLOGY

Luminaire type	Light bollard (single light emission)
Light source	1x LED module type BLK2-4/5/7/8S fixed, 1x LED module type BLK2-3/4/5/7/8S adjustable
Light colour	2'200 K / 2'700 K / 3'000 K, optional 1'800 K / 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	2'558 lm (2x BLK2-5S at 500 mA, example configuration as per datasheet)
Cover	luminaire glazing in clear PMMA, PMMA lenses satin-finished

FUNCTIONALITY

Dimmability	DALI, dimming circuit, AstroDim
Motion detector	Yes (optional, PIR sensor)
Interfaces	optional Zhaga socket, esave controller
Application area	Outdoor

DIMENSIONS

Width/depth	200 x 200 mm
-------------	--------------

Height	4'500 mm (reference version)
Light point height	4.35 m (reference version)

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
Housing material	steel, hot-dip galvanised, coated surfaces
Light emission material	luminaire glazing clear PMMA, lenses PMMA satin-finished
Luminaire body	steel

FURTHER DATA

Protection rating	housing IP65, LED module IP67
Protection class	I and II
Warranty	5 years
Certificates	CE, LED module and LED driver ENEC-certified
Mounting	bollard base (ground section) or flange plate

VARIANTS

65.09705.H18558 65.09705.H18558