

Rondo 150 LS

1 variant



The Rondo 150 LS is a round light bollard for outdoor lighting with a housing in coated aluminium (ø 150 mm) and luminaire glazing in satin-finished PMMA. It is equipped with one LED module of type BLF 110-12 with symmetric light distribution and covers a power of 29-41 W and a luminous flux of 2'510-3'370 lm. The light colour is fixed at 3'000 K warm white; 4'000 K neutral white is available as an option. The bollard can be supplied in heights of up to max. 3.5 m.

TECHNICAL DATA

ELECTRONICS

Power	29 - 41 W
Control gear	OSRAM OT50 2DIM (AstroDim, 1-10 V), optionally DALI + DC-capable, dimming circuit (StepDim)

LIGHTING TECHNOLOGY

Luminaire type	Light bollard (symmetric light distribution)
Light source	1x LED module type BLF 110-12
Light colour	3'000 K, optional 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	2'510 - 3'370 lm
Cover	luminaire glazing in PMMA, satin-finished

FUNCTIONALITY

Dimmability	AstroDim (1-10 V), optionally DALI, dimming circuit (StepDim)
Motion detector	No
Interfaces	optionally DALI
Application area	Outdoor

DIMENSIONS

Diameter	ø150 mm
----------	---------

Height	max. up to 3.5 m
Light aperture length	1'200 mm

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
Housing material	aluminium, coated surfaces
Light emission material	luminaire glazing PMMA, satin-finished
Luminaire body	aluminium

FURTHER DATA

Protection rating	housing IP65, LED module IP20
Protection class	I and II
Warranty	5 years
Certificates	CE
Mounting	ground section, flange plate or base plate (with/without ground spike)

VARIANTS

65.09706.H18559 65.09706.H18559