

Canna Q 150 PL

1 variant



The Canna Q 150 PL is a square light bollard for outdoor lighting with a housing in hot-dip galvanised and coated steel (150 x 150 mm) and luminaire glazing in clear PMMA. It is equipped with an LED module of type BLK2-4/5/6/8S and covers a power of 10.5-19.4 W and a luminous flux of 775-1'828 lm. The light colours 2'200/2'700/3'000 K (optionally 1'800/4'000 K) and several selectable light distributions make the luminaire versatile, for example for path and square lighting.

TECHNICAL DATA

ELECTRONICS

Power	10.5 - 19.4 W
Control gear	OSRAM OT40 4DIM (AstroDim, DALI), optionally DC-compatible, power reduction circuit (StepDim)

LIGHTING TECHNOLOGY

Luminaire type	Light bollard (square)
Light source	1x LED module type BLK2-4S / BLK2-5S / BLK2-6S / BLK2-8S
Light distribution	asym. extra-wide (only with glare shield BLC) / asym. wide (P) / asym. wide (P_4) / sym. wide
Light colour	2'200 K / 2'700 K / 3'000 K, optionally 1'800 K / 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	775 - 1'828 lm (depending on module)
Cover	luminaire glazing in clear PMMA, PMMA lenses satin-finished

FUNCTIONALITY

Dimmability	AstroDim, DALI, optionally power reduction circuit (StepDim)
Application area	Outdoor

DIMENSIONS

Cross-section	150 x 150 mm
Height	1'100 mm

Light aperture length	200 mm
-----------------------	--------

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
----------------	--

Housing material	steel, hot-dip galvanised and coated
------------------	--------------------------------------

Light emission material	luminaire glazing PMMA clear, PMMA lenses satin-finished
-------------------------	--

Luminaire body	steel
----------------	-------

FURTHER DATA

Protection rating	housing IP65, LED module IP67
-------------------	-------------------------------

Protection class	I and II
------------------	----------

Warranty	5 years
----------	---------

Certificates	CE
--------------	----

Mounting	flange plate with mounting shoe, with or without ground section
----------	---

VARIANTS

65.09714.H18567	65.09714.H18567
-----------------	-----------------