

ANS 200 PL

1 variant



The ANS 200 PL is a low light bollard for outdoor lighting with a round aluminium luminaire head (ø200 mm, height 65 mm) on a slender post (ø90 mm) and an underside cover in clear PMMA. It is equipped with an LED module of type BLK1-4 or BLK1-8 (C or S) and covers a power of 4.3-7.8 W and a luminous flux of max. 728-799 lm at 3'000 K. The light colours 2'200/2'700/3'000 K (optionally 1'800/4'000 K) make the luminaire flexible in use, for example for low-level path or accent lighting. The reference version is 1'018 mm high; further heights are available on request.

TECHNICAL DATA

ELECTRONICS

Power	4.3 - 7.8 W
Control gear	constant-current driver for LED modules, DALI dimmable, DC-compatible

LIGHTING TECHNOLOGY

Luminaire type	Light bollard (low disc shape)
Light source	1x LED module type BLK1-4 or BLK1-8, C or S
Light colour	2'200 K / 2'700 K / 3'000 K, optionally 1'800 K / 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	max. 728 - 799 lm (at 3'000 K, depending on module)
Cover	underside cover in clear PMMA, PMMA lenses clear or satin-finished

FUNCTIONALITY

Dimmability	DALI
Application area	Outdoor

DIMENSIONS

Head diameter	ø200 mm, height 65 mm
Post diameter	ø90 mm

Total height	1'018 mm, further heights on request
--------------	--------------------------------------

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
Housing material	aluminium profile, coated surfaces
Light emission material	underside cover PMMA clear, PMMA lenses clear or satin-finished
Luminaire body	aluminium

FURTHER DATA

Protection rating	housing IP54, LED module IP67
Protection class	I and II
Warranty	5 years
Certificates	CE
Mounting	separate ground section with cable junction box

VARIANTS

65.09715.H18568 65.09715.H18568