

Fellbach SL

1 variant



The Fellbach SL is a slender, wedge-shaped catenary luminaire for outdoor lighting that is mounted inline directly in the span wire (cable holder integrated). The housing in coated aluminium (length 600 mm) accommodates 2x LED module of type BLK2-1/3/4/5/6/8 (C or S) and covers a power of 21-40 W. The light colours 2'700/3'000 K (optionally 1'800/2'200/4'000 K) make the luminaire flexible in use, for example for urban street and square lighting with overhead spans. Reference project: Wüst Areal, Fellbach (2020).

TECHNICAL DATA

ELECTRONICS

Power	21 - 40 W
Control gear	OSRAM OT50 2DIM (AstroDim, 1-10V)

LIGHTING TECHNOLOGY

Luminaire type	Catenary luminaire, inline mounting directly on the span wire
Light source	2x LED module type BLK2-1/3/4/5/6/8, C or S
Light colour	2'700 K / 3'000 K, optionally 1'800 K / 2'200 K / 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Cover	PMMA lenses, clear or satin-finished

FUNCTIONALITY

Dimmability	AstroDim (1-10V)
Application area	Outdoor, inline catenary mounting (cable holder integrated)

DIMENSIONS

Length	600 mm
Height (cross-section)	55 mm
Weight	approx. 5.5 kg

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
Housing material	aluminium, coated
Light emission material	PMMA lenses clear or satin-finished
Luminaire body	aluminium
FURTHER DATA	
Protection rating	housing IP54, LED module IP67
Protection class	I
Warranty	5 years
Certificates	CE
Mounting	cable holder integrated; span wires and connection cables not included in the delivery (design variant D)

VARIANTS

65.09723.H18576 65.09723.H18576