

Rondo 250 SL

1 variant



The Rondo 250 SL is a cylindrical catenary luminaire for outdoor lighting with a housing in coated aluminium (ø250 mm) and a decorative glare-control tube in satin-finished PMMA. It is equipped with 2x LED module of type BLK3-1S or BLK3-6S and covers a power of 29-55 W and a luminous flux of 3'166-5'970 lm. The light colour is fixed at 3'000 K warm white; 4'000 K neutral white is available as an option. The luminaire is mounted on a cable suspension (design variant D).

TECHNICAL DATA

ELECTRONICS

Power	29 - 55 W
Control gear	OSRAM OT100 2DIM (AstroDim, 1-10V), optionally DALI + DC-compatible, power reduction circuit (StepDim)

LIGHTING TECHNOLOGY

Luminaire type	Catenary luminaire, cylindrical design
Light source	2x LED module type BLK3-1S or BLK3-6S
Light distribution	medium-wide deep-beam / sym. wide-beam
Light colour	3'000 K, optionally 4'000 K
Light colour adjustable	No
Power adjustable	Yes
Rated luminous flux	3'166 - 5'970 lm (depending on module)
Cover	decorative glare-control tube in satin-finished PMMA, PMMA lenses satin-finished

FUNCTIONALITY

Dimmability	AstroDim (1-10V), optionally DALI, power reduction circuit (StepDim)
Application area	Outdoor, catenary mounting

DIMENSIONS

Diameter	ø250 mm
----------	---------

Height	395 mm
--------	--------

MATERIAL

Housing colour	DB703 (BL anthracite) / DB702 (BL grey) / DB701 (BL silver-grey), further colours on request
Housing material	aluminium, coated surfaces
Light emission material	decorative glare-control tube in satin-finished PMMA, PMMA lenses satin-finished
Luminaire body	aluminium

FURTHER DATA

Protection rating	housing IP54, LED module IP66
Protection class	I and II
Warranty	5 years
Certificates	CE
Mounting	catenary mounting (design variant D)

VARIANTS

65.09725.H18578 65.09725.H18578